




Construction 	Options 1. Two kinds of pitch available as attached table <table border="1" data-bbox="560 936 855 1066"><thead><tr><th rowspan="2">Actuator Type</th><th colspan="2">Pitch (mm)</th></tr><tr><th>Standard</th><th>Option</th></tr></thead><tbody><tr><td>E</td><td>7.62</td><td>8.50</td></tr><tr><td>L</td><td>8.50</td><td>7.62</td></tr></tbody></table> 2. Special marking and body color available 3. Tape sealed	Actuator Type	Pitch (mm)		Standard	Option	E	7.62	8.50	L	8.50	7.62	 																													
Actuator Type	Pitch (mm)																																									
	Standard	Option																																								
E	7.62	8.50																																								
L	8.50	7.62																																								
<div>Obsolete</div> <div>MECHANICAL AND ENVIRONMENTAL DATA</div> <table><tr><td colspan="2">Electrical data</td><td colspan="2">Mechanical and Environmental data</td></tr><tr><td>Contact Rating</td><td></td><td>Operating temperature</td><td>- 25°C to +70°C</td></tr><tr><td>-switching</td><td>25 mA, 24 V DC</td><td>Storage temperature</td><td>- 40°C to +85°C</td></tr><tr><td>-non-switching</td><td>100 mA, 50 V DC</td><td>Operating force</td><td>800 gf max.</td></tr><tr><td>Contact Resistance</td><td></td><td>Operating life</td><td>2000 operations</td></tr><tr><td>-initial</td><td>50 mΩ max.</td><td>Vibration</td><td>10 Hz – 50 Hz – 10 Hz for 6 hours</td></tr><tr><td>-after life test</td><td>100 mΩ max.</td><td></td><td></td></tr><tr><td>Insulation Resistance</td><td>1000 MΩ min. at 100 V DC</td><td></td><td></td></tr><tr><td>Withstanding Voltage</td><td>500 V AC for 1 Minute</td><td></td><td></td></tr><tr><td>Capacitance between adjacent switches</td><td>5 pF max.</td><td></td><td></td></tr></table>			Electrical data		Mechanical and Environmental data		Contact Rating		Operating temperature	- 25°C to +70°C	-switching	25 mA, 24 V DC	Storage temperature	- 40°C to +85°C	-non-switching	100 mA, 50 V DC	Operating force	800 gf max.	Contact Resistance		Operating life	2000 operations	-initial	50 mΩ max.	Vibration	10 Hz – 50 Hz – 10 Hz for 6 hours	-after life test	100 mΩ max.			Insulation Resistance	1000 MΩ min. at 100 V DC			Withstanding Voltage	500 V AC for 1 Minute			Capacitance between adjacent switches	5 pF max.		
Electrical data		Mechanical and Environmental data																																								
Contact Rating		Operating temperature	- 25°C to +70°C																																							
-switching	25 mA, 24 V DC	Storage temperature	- 40°C to +85°C																																							
-non-switching	100 mA, 50 V DC	Operating force	800 gf max.																																							
Contact Resistance		Operating life	2000 operations																																							
-initial	50 mΩ max.	Vibration	10 Hz – 50 Hz – 10 Hz for 6 hours																																							
-after life test	100 mΩ max.																																									
Insulation Resistance	1000 MΩ min. at 100 V DC																																									
Withstanding Voltage	500 V AC for 1 Minute																																									
Capacitance between adjacent switches	5 pF max.																																									
FEATURES <table><tr><td><ul style="list-style-type: none">• Same size as an IC, 7.62mm (.300"), can be assembled by any automatic IC Inserter• Smaller size makes better heat convection during PC board wave soldering• Tape sealed to withstand solder vapors and board washing</td><td><ul style="list-style-type: none">• All plastics used are UL 94V-0 grade fire retardant• Twin contact design to ensure stable contact• Gold plated contacts to ensure low contact resistance, and tin plated terminal to prevent contamination during soldering (<i>gold/tin</i>)• Standard packing method Tube</td></tr></table>				<ul style="list-style-type: none">• Same size as an IC, 7.62mm (.300"), can be assembled by any automatic IC Inserter• Smaller size makes better heat convection during PC board wave soldering• Tape sealed to withstand solder vapors and board washing	<ul style="list-style-type: none">• All plastics used are UL 94V-0 grade fire retardant• Twin contact design to ensure stable contact• Gold plated contacts to ensure low contact resistance, and tin plated terminal to prevent contamination during soldering (<i>gold/tin</i>)• Standard packing method Tube																																					
<ul style="list-style-type: none">• Same size as an IC, 7.62mm (.300"), can be assembled by any automatic IC Inserter• Smaller size makes better heat convection during PC board wave soldering• Tape sealed to withstand solder vapors and board washing	<ul style="list-style-type: none">• All plastics used are UL 94V-0 grade fire retardant• Twin contact design to ensure stable contact• Gold plated contacts to ensure low contact resistance, and tin plated terminal to prevent contamination during soldering (<i>gold/tin</i>)• Standard packing method Tube																																									

How to order

DAH – 1 xx – XXxx Z

Contact Type	Nbr of positions	Actuator, Sealing and DIP Space
1 = SPST	see under position/dimension box above Example: 2 Position = 02 3 Position = 03 etc.	L = Low profile Actuator and DIP space 8.50mm LT = Low profile Actuator & Tape sealed & DIP space 8.50mm L01 = Low profile Actuator and DIP space 7.62mm LT01 = Low profile Actuator & Tape sealed & DIP space 7.62mm E = Extended Actuator and DIP space 7.62mm E01 = Extended Actuator and DIP space 8.50mm