



SPST Contact Form




Position	2	3	4	5	6
Dim. "A"	6.70	9.20	11.70	14.20	16.70
Position	7	8	9	10	12
Dim. "A"	19.20	21.70	24.20	26.70	31.80

Unit: mm




DPST Contact Form




Position	1	2	3	4	5	6
Dim. "A"	6.70	11.70	16.70	21.70	26.70	31.80

Unit: mm




SPDT Contact Form




Position	1	2	3	4	5	6
Dim. "A"	6.70	11.70	16.70	21.70	26.70	31.80


Unit: mm



Construction






PCB Hole Layout



Options

1. Top side "OFF" and "ON" available
2. Black body color available
3. Tape sealed



SPECIFICATIONS

Electrical data

Contact Rating	25 mA, 24 V DC
-switching	100 mA, 50 V DC
-non-switching	
Contact Resistance	50 mΩ max.
-initial	100 mΩ max.
-after life test	
Insulation Resistance	1000 MΩ min. at 100 V DC
Withstanding Voltage	500 V AC for 1 Minute
Capacitance between adjacent switches	5 pF max.

Mechanical and Environmental data

Operating temperature	- 25°C to +70°C
Storage temperature	- 40°C to +85°C
Operating force	800 gf max.
Mechanical life	1000 operations
Vibration	10 Hz – 50 Hz – 10 Hz for 6 hours

FEATURES


- Edge actuated (piano type) easy setting on closely racked PCB
- Tactile response is performed directly by larger contact pressure to ensure very stable contact
- All plastic are UL 94V-0 grade fire retardant
- Bottom epoxy sealed standard to ensure free of flux immersion during wave soldering
- Contact wiping on make and break
- Gold plated (gold/gold) or Tin plated contact to ensure low contact resistance and long operation life
- Ideal for Data Processing, Telecommunication, Remote Control and Burglar Alarm System use, where manual programming is required

How to order

DPX - X XX - XX Z


Series	Contact Form	Nbr of positions	"ON/OFF" Position and Sealing
DPG = Gold plated Contacts	1 = SPST	see under position/dimension box above	A = Top side OFF
DPS = Tin plated Contacts	2 = DPST	Example: 1 Position = 01 2 Position = 02 etc.	AT = Top side OFF & Tape sealed
	3 = SPDT		B = Top side ON
			BT = Top side ON & Tape sealed

DPDT Contact Form




Position	1	2	3
Dim. "A"	11.70	21.70	31.80

Unit: mm




3PST Contact Form




Position	1	2	3	4
Dim. "A"	9.20	16.70	24.20	31.80

Unit: mm




4PST Contact Form




Position	1	2	3
Dim. "A"	11.70	21.70	31.80


Unit: mm



Construction




PCB Hole Layout



Options

1. Black body color available

2. Tape sealed



Application

Ideal for Data Processing, Telecommunication, Remote Control and Burglar Alarm System use, where manual programming is required.

SPECIFICATIONS

Electrical data

Contact Rating	
-switching	25 mA, 24 V DC
-non-Switching	100 mA, 50 V DC
Contact Resistance	
-initial	50 mΩ max.
-after life test	100 mΩ max.
Insulation Resistance	1000 MΩ min. at 100 V DC
Withstanding Voltage	500 V AC for 1 Minute
Capacitance between adjacent switches	5 pF max.

Mechanical and Environmental data

Operating temperature	- 25°C to +70°C
Storage temperature	- 40°C to +85°C
Operating force	800 gf max.
Mechanical life	1000 operations
Vibration	10 Hz – 50 Hz – 10 Hz for 6 hours

FEATURES

- Edge actuated (piano type) easy setting on closely racked PCB
- Tactile response is performed directly by larger contact pressure to ensure very stable contact
- Bottom epoxy sealed standard to ensure free of flux immersion during wave soldering
- Contact wiping on make and break
- All plastics used are UL 94V-0 grade fire retardant
- Gold plated (gold/gold) or Tin plated contact to ensure low contact resistance and long operation life

How to order

DPX – x xx – XX Z

<p>Series</p> <p>DPG = Gold plated Contacts</p> <p>DPS = Tin plated Contacts</p>	<p>Contact Form</p> <p>4 = 3PST</p> <p>5 = 4PST</p> <p>6 = DPDT</p>	<p>Nbr of positions</p> <p>see under position/dimension box above</p> <p>Example: 1 Position = 01 2 Position = 02 etc.</p>	<p>Actuator and Sealing</p> <p>A = Top side OFF</p> <p>AT = Top side OFF & Tape sealed</p> <p>B = Top side ON</p> <p>BT = Top side ON & Tape sealed</p>
---	---	---	--